

Autocar MY 2016 6x4 2013 DOT/EPA Compliant Terminal Tractor Standard Specifications

Engine and Equipment	Standard	Optional
Engine model	Cummins 2013 ISB diesel - 200 HP @ 2600 RPM 520 ft-lb torque @ 1600 RPM	Cummins 2013 ISB diesel - 260 HP @ 2600 RPM 660 ft-lb torque
Exhaust	Horizontal DPF w/ vertical SCR; 5 gallon DEF tank, right side mounted	Horizontal DPF w/ vertical SCR; 10 gallon DEF tank, right side mounted 11" 2 stage/Donaldson inline precleaner/Donaldson topspin precleaner
Air cleaner	Donaldson 11 inch single stage	
Radiator	1050 sq in copper brass	
Fan & drive	Viscous fan drive (Required to pass DOT noise test)	
Coolant hoses/piping	Silicone hoses with steel tubing	
Coolant	Extended life coolant	

Transmission and Equipment

Transmission model	Allison 3000 RDS	<i>(Allison 3500 RDS)</i>
Transmission gearing	4-speed	<i>(3-speed 4 speed or 5-speed)</i>
Transmission controls	Allison push button (Gen V)	<i>(Allison t-handle)</i>
Transmission cooler	Oil to water type	
Transmission lubricant	TranSynd™ synthetic	
Driveshaft	Dana Spicer® 1710 half-round	

Front Axle and Equipment

Axle model	Meritor MFS 14	<i>Dana Spicer® E-1322-W (13,200 lb rated)</i>
Front suspension	Flat leaf (14,500 lb rated)	
Shock absorbers	None	Double acting - heavy duty
Power steering	Gearbox, integral steering w/ mechanical backup	
Power steering reservoir	Integral w/ hydraulic tank	
ABS	Bendix 4S4M w/o traction control	<i>(required for vehicle speeds over 33 MPH)</i>
Brakes	16.5 x 5 s-cam	
Brake drums	Cast iron	
Slack adjusters	Automatic slack adjusters	
Front hubs	Iron hub piloted	

Rear Axle and Equipment

Axle model	Meritor MT40-14X (single reduction)	
Rear axle ratio	7.17:1	
Rear suspension	Hendrickson HN460 54" spread	
ABS	Bendix 4S4M w/o traction control	<i>(required for vehicle speeds over 33 MPH)</i>
Brakes	16.5x8.62	16.5x7
Brake drums	Cast iron	
Slack adjusters	Automatic slack adjusters	
Rear hubs	Iron hub piloted	
Gear lubricant	Synthetic	

Chassis and Equipment

Wheelbase	146	
Frame	2.0 million RBM, 50,000 KSI steel, 'C'-reinforced	
Frame fasteners	Huck bolts where possible	
Bumper	Steel reinforced bumper	Heavy duty reinforced bumper
Tow device(s)	Front & rear tow eyes	
Mud flaps	Rear of drive tires	
Brake system	121 air brake system, front/rear system protection	

Pneumatic System (Rapid Fill)

Air compressor	Wabco 18.7 CFM	
Air system drain valve	Manual petcocks all tanks	Manual pull cords on all tanks
Air lines	Nylon, color coded	

Fuel System

Fuel tank	50 gallon steel rectangular w/ deep step, left side mounted	
Fuel filter	Cummins	Davco 382 w/Heat
Fuel lines	SAE J844 nylon	

5th Wheel and Hydraulic System

5th wheel	SAF/Holland 70,000 lb semi-oscillating 16 inch lift bearings	(SAF/Holland 100,000 lb)
Hydraulic lift cylinders	(2) 5 inch 50,000 lb capacity, upper & lower spherical bushings	(limited lift height cylinders)
Hydraulic tank	15 gallon steel tank w/ sight glass	
Pump	Engine mounted	Transmission mounted PTO

Trailer Equipment

Air connections	15' straight rubber trailer hoses w/spring hangers	12 ft color coded coiled w/ glad-hands
7-way electric cable receptacle	7-way electric cable 12 FT	12 ft coiled detachable

Tires and Wheels

Front tires	11R22.5 LRG
Front wheels	Steel 22.5 x 8.25 hub piloted, 285mm BC
Rear tires	11R22.5 LRG
Rear wheels	Steel 22.5 x 8.25 hub piloted, 285mm BC

Electrical System

Electrical System	12V, negative ground	
Alternator	Delco Remy 22SI 130AMP	
Starter	Denso 12V	
Batteries	(2) group 31 950 CCA (min)/1900 CCA total	(2) group 31 1000 CCA 2000 CCA total
Circuit protection	Automatic circuit breakers	
Windshield wipers	Single electric (pantograph) intermittent w/washer	
Backup alarm	Non-motion detecting	
Horn	Single	

Lighting

Headlamps	Low/high halogen	
Backup light, stop & turn signals	LED stop & turn, incandescent backup, shock resistant mount	(LED backup)
BOC 5th wheel light	Incandescent, shock resistant mount	(LED backup)
Marker and side turn signals	LED	

Cab and Equipment

Cab construction	• Electrocoated (e-coated) steel, full cab immersion • (Rust Prevention Coating)	
Cab dimensions (outside)	Raised roof, 52" wide x 71" deep (w/o rear door) x 78" high (deck to roof)	
Cab doors	Left side hinged door w/ manual crank window, sliding rear door	
Rear door opening (useable)	24" wide x 72" high	
Cab floor	Sweep out floor w/ durable mat	
Cab dash	Steel wrap around	
Overhead console	Steel	
Cab mounting	4 point, rear dual (2) air suspensions	3 point rear spring mount
Cab tilt	Electric over hydraulic	
Glass	Tinted, laminated windshield	
Mirrors	Dual SST west coast mirrors	(heated primary, motorized primary, convex)
Cab climate control system	44,000 BTU fresh air heater	(air conditioning)
Steering column	Fixed	Tilt/telescopic
Steering wheel	18 inch 2-spoke	
Seat	Air suspension, mid-back without fore/aft isolation	(air suspension, mid-back with fore/aft isolation)
Seat covering	Black Cordura Plus® cloth fabric	
Seat belt	3-point orange	
Dome light	Switch on dash	
Power ports	(2) 12V	
Air horns	Mounted under cab	Mounted top right right of cab
Translucent sun visor	Single	
Conspicuity tape		

Operators Controls

Park brake - push/pull
Headlamps
Turn signal - column mounted
Brake pedal
Accelerator pedal
5th wheel height control
5th wheel lock
Transmission gear selector - Push button

Cab Instrumentation

Speedometer
Tachometer
Engine oil pressure
Coolant temperature
Transmission oil temperature
Voltmeter
Fuel level/ DEF level
Primary (A) air pressure
Secondary (B) air pressure
Hour meter (included in tachometer)

Cab Warning Devices

Park brake
High beam
Turn signal
Low fuel
Low air
Seat belt
DPF
HEST
Air restriction indicator
Filter with water in fuel indicator

Paint

Cab	White	(customer specific colors)
Chassis	Black	(customer specific colors)
Bumper	Black	(customer specific colors)
Wheels	White powder coat	(customer specific colors)

Optional Equipment

Air Dryer	Glad-hand and 7-way cable storage	Cab fan
Engine block heater	Battery disconnect switch	AM/FM radio/CD w/ aux input, speakers & antenna
Oil pan heater	Air restriction indicator w/ dash light	5# ABC fire extinguisher
Rear flexible fenders	Amber beacon light	Additional instrumentation
Trailer stops/full cab guard	Spot/work/flood lights	Lever start, no key
Glad hand buckets	Rear door laminated glass	Double blink strobe light
Safety yellow decking and grabhandles	Auto lube system	Trailer hand brake
Rapid air trailer fill system		

Vehicle Ratings

Vehicle tare weight, front	
Vehicle tare weight, rear	
GAWF	13,200 lbs
GAWR	40,000lbs
GCW	80,000 lbs

Performance

Basic Warranties (Industry Best)

Autocar terminal tractor	1 year or 3,000 hours whichever occurs first, parts & labor
Cummins engine	2 years parts & labor
Dana axles	3 years parts & labor
Allison transmission	4 years parts & labor
Frame	7 years or 20,000 hours whichever occurs first
Meritor Axles	2 years parts & labor

